shat r-shield lighting inc.

Project	

Туре

Date	
Notes	



VR Pro™ ∨andal-Resistant LED Correctional Cell Light

The Ironclad[®] VR Pro Vandal-Resistant correctional cell and behavioral room fixture uses an LED high efficiency light engine with a light that simulates daylight. The incorporated count light LED module gives off a soothing warm light that can be turned on and off as needed.

Construction

One piece Mounting Ring- .500" thick 304 Stainless Steel

Lens- .400" thick cast, diffused translucent, Highly Engineered Polyurethane. Shore hardness D80+, tensile strength 5,400 psi, impact strength 55 in. lbs./ in. Mounting- .125" aluminum heat sink to maintain thermal management Installation- Anchored flush onto ceiling with (8) recessed tamper-proof 1/4"

concrete drive anchors or (8) 1/4" tamper-proof stainless steel bolts Wiring- Hard wired direct to AC current; eliminating failure points via driver

Features- No accessible parts, No rusting or peeling paint, Count Light

Specifications

- Extreme Durability- hammer & knife tested
- 80 CRI

Uı

C

- No areas to hide or conceal contraband.
- Weight: 7.9 lbs.

US

• Dimensions: 12.25" diameter x 1.9" tall

UL Wet

Locations

UL Damp Locations

Ordering Guide



Watts	35W or 42W			
Voltage	120 or 277V			
Lumens	3,600			
Color Temperatures	5000K, 4000K, 3500K or 2700K; Count Light 2700K			
LED Life	L70>75,000 Hours; Projected>100,000 Hours			
Footcandles	35 ftc at the desk level; 22 ftc at the floor			
Warranty	5 year limited warranty			

```
Manufactured in America with globally and domestically sourced components
```

Wattage	Fixture	ССТ	Mount	Count Light	Voltage	Ring Material	Lens	Access.	Access.	Access.	Rev	
	VR									00	01	
Va		50 = 5000K	CL = Ceiling						00 = None			
		VR = Vandal Resistant 35 = FT = Flat	Y = Yes	VH =	SS = 304 Stainless	UR = Urethane	00 = None	TB = Tamper-proof Bolts & Inserts				
					P1 = Powder Coat, SS, Black			CF = Cinder				
	Vandal Resistant			:		P2 = Powder Coat, SS,]	Block Fasteners	00 = None		
		3500K	Тор			White	White	PC =		SA =		
		27 = FW = 2700K Flat Wall	N = No		P5 = Powder Coat, SS,	Polycarbonate	JB = Surface Box Kit	Spike Anchors				
				Brown		BOX KIL	MS = Metal Ceiling Screws					

www.shatrshield.com (800) 223-0853 ©2023 Shat-R-Shield Lighting Inc.