

# 100LB50PHNCVLN060002

100W/LED HBPRIS/VL/5000K GEN2



**Ambient Temp. Range:** -40 to 122 °F

**Average Life Hours:** 50000

**Beam Angle:** 103

**Color:** Black/Silver

**CRI:** 80

**Dimmable:** Yes

**Fixture Watts:** 100.0

**Lamp Type:** LED

**Material:** Die Cast Aluminum

**Mounting:** Hook

**Package (LxWxH):** 19.25 IN x 19.25 IN x 16.00 IN

**Power Factor:** 0.9

**Power Source:** LED Driver

**Shape:** Low Bay

**Style:** 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

**Type:** 100W LED Low Bay, High Bay Prismatic, No Lens Cover

**Voltage:** 120-277 V

**Width:** 16.50 IN

**Application:** Low Bay Lighting

**Driver Type:** LED Driver

**Bulb:** LED

**Color Temperature:** 5000K

**Diameter:** 16.50 IN

**Fixture Type:** 100W LED Low Bay, High Bay Prismatic, No Lens Cove, 120-277V

**Frequency Rate:** 50/60

**Length:** 19.25 IN

**Lumens:** 11660

**Number of Lamps:** 1

**Package Weight:** 32.25 L

**Pack By:** 1

**Reflector Type:** Prismatic

**Special Features:** 6" Cord

**Temperature Range:** -40 to 122 °F

**UPC:** 726585100040

**Wattage:** 100.0 W

CULUS,UL Damp Location,ROHS,DLC,Lighting Facts