



# 57017

F48T12 CW/HO/ALTO/TSC (PK X 30)



<b>Ambient Temp. Range:</b>		<b>Amps:</b>	
<b>Application:</b>	Industrial, Food Processing, Food Service, Retail, Hospitality, General Lighting	<b>Average Life Hours:</b>	14000
<b>Ballast Type:</b>		<b>Base:</b>	Recessed Double Contact (R17d)
<b>Battery:</b>		<b>Beam Angle:</b>	
<b>Bulb:</b>	T12	<b>Coating:</b>	Copolymer
<b>Color:</b>	Cool White	<b>Kelvin:</b>	4100 K
<b>Construction:</b>		<b>CRI:</b>	62
<b>Diameter:</b>	1.50 IN	<b>Dimmable:</b>	
<b>Effective Arc Length:</b>		<b>Enclosure:</b>	
<b>Environmental Conditions:</b>		<b>Filament Type:</b>	
<b>Finish:</b>		<b>Fixture Type:</b>	
<b>Fixture Watts:</b>		<b>Field Wiring:</b>	
<b>Focus:</b>		<b>Frequency Rate:</b>	
<b>Height:</b>		<b>Housing Color:</b>	
<b>Housing Material:</b>		<b>Housing Finish:</b>	
<b>Incan Wattage Equivalent:</b>		<b>Initial Lumens:</b>	4050
<b>Pack By:</b>	30	<b>Weight:</b>	0.833
<b>Inventory Specification:</b>		<b>Lamp Type:</b>	Fluorescent
<b>Lamp Wattage:</b>		<b>Length:</b>	48.00 IN
<b>Lens Material:</b>		<b>Light Center Length:</b>	
<b>Material:</b>		<b>Mean Lumens:</b>	3500
<b>Mount:</b>		<b>SDS:</b>	<a href="#">Download SDS</a>
<b>Number of Lamps:</b>		<b>Operating Position:</b>	
<b>Package Dimensions:</b>	49.50 x 8.75 x 10.25	<b>Package Weight:</b>	24.70 L
<b>Power Factor:</b>		<b>Power Rating:</b>	
<b>Power Sources:</b>		<b>Radiation Specification:</b>	
<b>Reflector Type:</b>		<b>Shape:</b>	T
<b>Size:</b>		<b>Socket Type:</b>	
<b>Special Features:</b>	Shatter-Resistant	<b>Start Type:</b>	
<b>Style:</b>		<b>Temperature Range:</b>	

---

<b>Total Harmonic Distortion:</b>		<b>Type:</b>	Straight Linear Fluorescent Lamp
<b>UNSPSC:</b>	39101605	<b>UPC:</b>	726585570171
<b>Volts:</b>		<b>Wattage:</b>	60.0
<b>Width:</b>		<b>Warm Up Time:</b>	
<b>ProdCI:</b>	01		

ULEPH,ROHS,NSF Non-Food Zone,NSF Splash Zone