



Ironclad® High Bay/Flood Light

The **Ironclad® High Bay/Flood Light** is a high lumen output system that combines two designs. This fixture's ability to cover large areas by utilizing high lumen outputs and versatile beam angles allows for maximum coverage in high mounting applications such as hangers, building exteriors and open recreational areas.

- Specifically designed to replace 1000W and 2000W HID/Metal Halide Lamps.
- Features an **IP65** rating to withstand dust and low pressure wash downs
- **IK08** rating for high impact resistance.

Specifications:

- 450W/72,000 Lumens or 600W/96,000 Lumens
- 5000K CCT, 70 CRI
- 100-277VAC, 50/60 Hz
- Dimmable, Daylight Sensor, Microwave Sensor, PIR Sensor, Wireless Control
- L70>36,000 Hours
- Operating Temp: -22°F to 113°F (-30°C to 45°C)
- Dimensions: 18" diameter x 10" Tall
- Weights: Bracket- 4.7lbs., Visor- 1.95 lbs., Main Unit- 29 lbs.
- Warranty: 5 year limited warranty

Applications: Processing Plants, Manufacturing, Packaging Plants, Warehouses, Hangars, Industrial Facilities, Cold Storage, Airports, Wash Down Areas, High Bay Applications, Large Open Recreational areas and many others where high output requirements may be needed.

Certifications: DLC, IP65 Dust-proof & Pressure Jets and IK08 5 Joules of impact resistance.

Mounting Options

Suspended



Bracket & Reflector



Part Numbers:

- FX848HBFL450W (450W Option)
- FX848HBFL450W-BRKT-VISOR (450W w/ bracket & reflector)
- FX848HBFL450W-MT BRKT (450W w/ bracket)
- FX848HBFL450W-VISOR (450W w/ reflector)
- FX849HBFL600W (600W Option)
- FX849HBFL600W-BRKT-VISOR (600W w/ bracket & reflector)
- FX849HBFL600W-MT BRKT (600W w/ bracket)
- FX849HBFL600W-VISOR (600W w/ reflector)

