

Project		Date	
Type		Notes	

GDL General Duty Linear

The Ironclad® General Duty Linear light or G.D.L is designed primarily for larger areas in correctional and behavioral applications. The fixture's extreme low profile and compact housing is made to withstand abuse and features a rimless edge providing a rugged lighting solution.

Construction

Lens- Highly impact-resistant 1/4" thick polycarbonate with a minimum IK10 impact rating

Installation- Anchored flush onto ceiling with (10) spike anchors or optional recessed tamper-proof 1/4" stainless steel bolts or cinder block fasteners or optional pendant mount


Features- No accessible parts or hinges
 - No maintenance needed

Specifications

- Extreme Durability- hammer & knife tested.
- No areas to hide or conceal contraband.
- Dimensions: 24.25" long x 11.6" wide x 2.2" tall



Watts	40W, 80W
Voltage	120-277V
Lumens	3800, 7400 Count Light: 530
Color Temperatures	5000K, 4000K Count Light: 2700K
LED Life	L70>75,000 Hours; Projected>100,000 Hours
Footcandles	35 ftc at the desk level; 22 ftc at the floor
Warranty	5 year limited warranty

 Manufactured in America with globally and domestically sourced components

Ordering Guide

Wattage	Fixture	CCT	Mount	Count Light	Voltage	Lens	Access.	Access.	Access.	Rev
	GDL		CM		VH	PC			00	02
040 = 40W	GDL = General Duty Linear	50 = 5000K	CM = Center	Y = Yes (Only in 40W units)	VH = 120- 277V	PC = Polycarbonate	00 = None	00 = None	00 = None	
080 = 80W		40 = 4000K		N = No			JB = Surface Box Kit	TB = Tamper-proof Bolts & Inserts		
							PM = Pendant Mount	SA = Spike Anchors		
							CB = Corner Box	CF = Cinder Block Fasteners		
							1W= 1 foot Whip	HD = Hammer Drive		
							2W= 2 foot Whip	MS = Metal Ceiling Screws		
							SW = Sample Whip			