



<b>Project</b>		<b>Date</b>	
<b>Type</b>		<b>Notes</b>	

## H2O Pro™ Vandal-Resistant LED Shower Light

The Ironclad® H2O Pro Shower Fixture is specifically designed for installation in correctional facility shower areas, this fixture is IP66 rated for water resistance against high pressure water jets. Also built to be highly impact-resistant with its 1/4" thick polycarbonate lens and virtually impenetrable 304 stainless steel outer ring and tamper-proof bolts, facilities will benefit from its safety and rugged nature even in high security area shower units.

### Construction

**One piece Mounting Ring-** .500" thick 304 Stainless Steel

**Lens-** Highly impact-resistant 1/4" thick polycarbonate with an IK10 impact rating

**Mounting-** Aluminum heat sink to maintain thermal management

**Installation-** Anchored flush onto ceiling with (6) recessed tamper-proof bolts or (6) spike anchors

**Wiring-** Hard wired direct to AC current; eliminating failure points via driver

**Features-** No accessible parts or hinges


- No rusting or peeling paint

### Specifications

- Extreme Durability- hammer & knife tested.
- No areas to hide or conceal contraband.
- Weight: 3 lbs. 10 oz.
- Dimensions: 9.25" diameter x 1.9" tall

<b>Watts</b>	24W, 35W
<b>Voltage</b>	120-277V
<b>Lumens</b>	2000, 2800
<b>Color Temperatures</b>	5000K, 4000K, 3500K or 2700K
<b>LED Life</b>	L70>75,000 Hours; Projected>100,000 Hours
<b>Footcandles</b>	25 ftc at the floor
<b>Warranty</b>	5 year limited warranty



 Manufactured in America with globally and domestically sourced components

### Ordering Guide

Wattage	Fixture	CCT	Mount	Lens	Voltage	Ring Material	Lens	Access.	Access.	Access.	Rev
	<b>H2O</b>			<b>F</b>	<b>VH</b>				<b>00</b>	<b>00</b>	<b>01</b>
24 = 24W		50 = 5000K	CL = Ceiling	F = Frosted	VH = 120-277V	SS = 304 Stainless Steel	PC = Polycarbonate	00 = None	00 = None	00 = None	
		40 = 4000K	WL = Wall			P1 = Powder Coat, SS, Black		TB = Tamper-proof Bolts & Inserts	JB = Surface Box Kit		
35 = 35W	H2O = Wet Location	35 = 3500K	FT = Flat Top			P2 = Powder Coat, SS, White		UR = Urethane	CF = Cinder Block Fasteners		
		27 = 2700K	FW = Flat Wall			P3 = Powder Coat, SS, Brown	SA = Spike Anchors		DL = Downlight Surface Box Kit		
								MS = Metal Ceiling Screws			