



| | | | |
|----------------|--|--------------|--|
| Project | | Date | |
| Type | | Notes | |

Puck Pro LED Utility Area Light

The Ironclad® Puck Pro fixture uses an LED high efficiency light engine and has a very low profile and small footprint. The Puck Pro is designed to withstand abuse and drastically delay, tampering, removal or damaging of a light fixture. The mounting ring is .50" thick Stainless Steel with recessed tamper-proof hardware. The lens is made .25" high impact polycarbonate. The fixture is completely sealed and UL rated for wet locations with an IP69K rating. The unique design eliminates all areas where contraband can be hidden.

Construction

Lens- Highly impact-resistant .236" thick polycarbonate with a minimum IK10 impact rating

Mounting- .125" aluminum heat sink to maintain thermal management

Installation- Anchored flush onto ceiling with (3) spike anchors or optional recessed tamper-proof 1/4" stainless steel bolts or cinder block fasteners

Wiring- Hard wired direct to AC current; eliminating failure points via driver

Features- No accessible parts or hinges
- No maintenance needed

Specifications

- Extreme Durability- hammer & knife tested.
- No areas to hide or conceal contraband.
- Dimensions: 6.38" diameter x 1.44" tall

| | |
|---------------------------|--|
| Watts | 10W |
| Voltage | 120-277V |
| Lumens | 600 |
| Color Temperatures | 4000K, 2700K |
| LED Life | L70>54,000 Hours; Projected>100,000 Hours |
| Warranty | 5 year limited warranty |



Manufactured in America with globally and domestically sourced components.

Ordering Guide

| Wattage | Fixture | CCT | Voltage | Frame | Lens | Access. | Access. | Rev |
|------------|---------------|------------|---------------|---------------------------|--------------------|-----------------------------------|-----------|-----------|
| 010 | PK | | VH | | PC | | 00 | 01 |
| 010 = 10W | PK = Puck Pro | 40 = 4000K | VH = 120-277V | S0 = Stainless Steel, 304 | PC = Polycarbonate | 00 = None | 00 = None | |
| | | | | S1 = Powder Coat, Black | | TB = Tamper-proof Bolts & Inserts | | |
| | | | | S2 = Powder Coat, White | | SA = Spike Anchors | | |
| | | | | S3 = Powder Coat, Bronze | | MG = Magnets | | |
| | | 27 = 2700K | | | | CF = Cinder Block Fasteners | | |
| | | | | | | MS = Metal Ceiling Screws | | |